

The following is a complete listing of all claims in the application, with an indication of the status of each:

**Listing of claims:**

- 1           1. (canceled)
- 2           2. (Original) A network connection system for connecting a first  
3           communication network and a plurality of user terminals when a second  
4           communication network is interposed between said first communication  
5           network and said plurality of user terminals, said second communication  
6           network employing a second protocol different from a first protocol employed  
7           in said first communication network, said system comprising:  
8                 a scheduling apparatus including:  
9                 a classification processing unit for classifying data conforming  
10                to said first protocol received from said communication network based  
11                on quality guaranteed classes set thereto;  
12                an overhead amount correction unit for correcting an overhead  
13                amount between a data rate associated with said first protocol and a  
14                data rate associated with said second protocol to convert received rate  
15                information on said second protocol to the rate based on said first  
16                protocol;  
17                a weighting coefficient calculation unit for calculating a  
18                weighting coefficient based on said rate calculated by said overhead  
19                amount correction unit such that a minimally guaranteed rate is assured  
20                for a minimum rate guaranteed class among classes classified by said  
              classification processing unit;

21 a weighting scheduler for scheduling data conforming to said  
22 first protocol of said minimum rate guaranteed class and of a  
23 weighting applied class among said classified classes based on the  
24 weighting coefficient calculated by said weighting coefficient  
25 calculation unit to deliver the data in accordance with the scheduling;  
26 and  
27 a scheduler for scheduling the data conforming to said first  
28 protocol from said weighting scheduler such that the data conforming  
29 to said first protocol is delivered at a transmission rate equal to or  
30 lower than said rate calculated by said overhead amount correction unit  
31 to deliver the data in accordance with the scheduling;  
32 a protocol converter for converting the data conforming to said first  
33 protocol after said scheduling apparatus has shaped the transmission rate  
34 therefor to data conforming to said second protocol; and  
35 a multiplexer including a current data detector for supplying said  
36 scheduling apparatus with said rate information as indicative of a currently set  
37 reception rate for said user terminals, said multiplexer being configured to  
38 transmit to each of said user terminals the data conforming to said second  
39 protocol from said protocol converter or the data conforming to said first  
40 protocol after said scheduling apparatus has shaped the transmission rate  
41 therefor.

1 3. (Original) A network connection system for connecting a first  
2 communication network and a plurality of user terminals when a second  
3 communication network is interposed between said first communication  
4 network and said plurality of user terminals, said second communication  
5 network employing a second protocol different from a first protocol employed  
6 in said first communication network, said system comprising:

7 a scheduling apparatus including:

8 a classification processing unit for classifying data conforming

9 to said first protocol received from said communication network based

10 on quality guaranteed classes set thereto;

11 an overhead amount correction unit for correcting an overhead

12 amount between a data rate associated with said first protocol and a

13 data rate associated with said second protocol to convert received rate

14 information on said second protocol to the rate based on said first

15 protocol;

16 a weighting coefficient calculation unit for calculating a

17 weighting coefficient based on said rate calculated by said overhead

18 amount correction unit such that a minimally guaranteed rate is assured

19 for the minimum rate guaranteed class among classes classified by said

20 classification processing unit;

21 a weighting scheduler for scheduling data conforming to said

22 first protocol of said minimum rate guaranteed class and of a

23 weighting applied class among said classified classes based on the

24 weighting coefficient calculated by said weighting coefficient

25 calculation unit to deliver the data in accordance with the scheduling;

26 and

27 a preferential control scheduler for scheduling the data

28 conforming to said first protocol from said weighting scheduler, and

29 data conforming to said first protocol of a best-effort class among said

30 classified classes such that the data conforming to said first protocol is

31 delivered at a transmission rate equal to or lower than said rate

32 calculated by said overhead amount correction unit, and for

33 preferentially scheduling the data conforming to said first protocol

34 from said weighting scheduler, and delivering the data conforming to

35                   said first protocol of the best-effort class at a timing at which there is  
36                   no data conforming to said first protocol from said weighting  
37                   scheduler;  
38                   a protocol converter for converting the data conforming to said first  
39                   protocol after said scheduling apparatus has shaped the transmission rate  
40                   therefor to data conforming to said second protocol; and  
41                   a multiplexer including a current data detector for supplying said  
42                   scheduling apparatus with said rate information as indicative of a currently set  
43                   reception rate for said user terminals, said multiplexer being configured to  
44                   transmit to each of said user terminals the data conforming to said second  
45                   protocol from said protocol converter or the data conforming to said first  
46                   protocol after said scheduling apparatus has shaped the transmission rate  
47                   therefor.

1                   4. (Original) A network connection system for connecting a first  
2                   communication network and a plurality of user terminals when a second  
3                   communication network is interposed between said first communication  
4                   network and said plurality of user terminals, said second communication  
5                   network employing a second protocol different from a first protocol employed  
6                   in said first communication network, said system comprising:  
7                   a scheduling apparatus including:  
8                   a classification processing unit for classifying data conforming  
9                   to said first protocol received from said communication network based  
10                  on quality guaranteed classes set thereto;  
11                  a rate measuring unit for measuring a transmission rate for a  
12                  preferential class among said classified classes;  
13                  an overhead amount correction unit for correcting an overhead  
14                  amount between a rate based on said second protocol and a rate based

NEC04P018-H1a

**AFTER FINAL: EXPEDITED ACTION**

01480088aa

Amendment dated 08/26/2008

Reply to office action mailed 06/09/2008

on said first protocol to convert received rate information on said second protocol to the rate based on said first protocol;

a weighting coefficient calculation unit for calculating a weighting coefficient based on said rate calculated by said overhead amount correction unit and the transmission rate for the preferential class measured by said rate measuring unit such that a minimally guaranteed rate is assured for the minimum rate guaranteed class among the classes classified by said classification processing unit;

a weighting scheduler for scheduling data conforming to said first protocol of said minimum rate guaranteed class and of a weighting applied class among said classified classes based on the weighting coefficient calculated by said weighting coefficient calculation unit to deliver the data in accordance with the scheduling; and

a preferential control scheduler for scheduling the data conforming to said first protocol of said preferential class, the data conforming to said first protocol from said weighting scheduler, and data conforming to said first protocol of a best-effort class among said classified classes such that the data conforming to said first protocol is delivered at a transmission rate equal to or lower than said rate calculated by said overhead amount correction unit, and for preferentially scheduling the data conforming to said first protocol of said preferential class, preferentially scheduling the data conforming to said first protocol from said weighting scheduler at a timing at which there is no data conforming to said first protocol of said preferential class, and delivering the data conforming to said first protocol of the best-effort class at a timing at which there is no data conforming to said first protocol from said weighting scheduler;

43 a protocol converter for converting the data conforming to said first  
44 protocol after said scheduling apparatus has shaped the transmission rate  
45 therefor to data conforming to said second protocol; and  
46 a multiplexer including a current data detector for supplying said  
47 scheduling apparatus with said rate information as indicative of a currently set  
48 reception rate for said user terminals, said multiplexer being configured to  
49 transmit to each of said user terminals the data conforming to said second  
50 protocol from said protocol converter or the data conforming to said first  
51 protocol after said scheduling apparatus has shaped the transmission rate  
52 therefor.

1 5. (Original) A network connection system for connecting a first  
2 communication network and a plurality of user terminals when a second  
3 communication network is interposed between said first communication  
4 network and said plurality of user terminals, said second communication  
5 network employing a second protocol different from a first protocol employed  
6 in said first communication network, said system comprising:  
7 a scheduling apparatus including:  
8 a classification processing unit for classifying data conforming  
9 to said first protocol received from said communication network based  
10 on quality guaranteed classes set thereto;  
11 a rate measuring unit for measuring a transmission rate for a  
12 preferential class among said classified classes;  
13 an overhead amount correction unit for correcting an overhead  
14 amount between a rate based on said second protocol and a rate based  
15 on said first protocol to convert received rate information on said  
16 second protocol to the rate based on said first protocol;

NEC04P018-H1a

**AFTER FINAL: EXPEDITED ACTION**

01480088aa

Amendment dated 08/26/2008

Reply to office action mailed 06/09/2008

17 a preferential class upper limit setting unit, operative when the  
18 difference between the transmission rate of the data conforming to said  
19 first protocol of the preferential class as measured by said rate  
20 measuring unit and said rate calculated by said overhead amount  
21 correction unit is lower than a minimally guaranteed rate for a  
22 minimum rate guaranteed class among the classes classified by said  
23 classification processing unit, for setting an upper limit to the  
24 transmission rate for said preferential class for shaping, such that the  
25 minimally guaranteed rate can be assured for said minimum rate  
26 guaranteed class;

27 a weighting coefficient calculation unit, operative when said  
28 preferential class upper limit setting unit does not set the upper limit,  
29 for calculating a weighting coefficient based on said rate calculated by  
30 said overhead amount correction unit and the transmission rate for the  
31 preferential class measured by said rate measuring unit such that the  
32 minimally guaranteed rate is assured for the minimum rate guaranteed  
33 class among the classes classified by said classification processing  
34 unit, said weighting coefficient calculation unit being further operative  
35 when said preferential class upper limit setting unit sets the upper  
36 limit, for calculating a weighting coefficient based on said rate  
37 calculated by said overhead amount correction unit and the upper limit  
38 rate set by said preferential class upper limit setting unit such that the  
39 minimally guaranteed rate is assured for said minimum rate guaranteed  
40 class;

41 a weighting scheduler for scheduling data conforming to said  
42 first protocol of said minimum rate guaranteed class and of a  
43 weighting applied class among said classified classes based on the  
44 weighting coefficient calculated by said weighting coefficient

45 calculation unit to deliver the data in accordance with the scheduling;  
46 and  
47 a preferential control scheduler for scheduling the data  
48 conforming to said first protocol of said preferential class, the data  
49 conforming to said first protocol from said weighting scheduler, and  
50 data conforming to said first protocol of a best-effort class among said  
51 classified classes, such that the data conforming to said first protocol is  
52 delivered at a transmission rate equal to or lower than said rate  
53 calculated by said overhead amount correction unit, and for  
54 preferentially scheduling the data conforming to said first protocol of  
55 said preferential class, preferentially scheduling the data conforming to  
56 said first protocol from said weighting scheduler at a timing at which  
57 there is no data conforming to said first protocol of said preferential  
58 class, and delivering the data conforming to said first protocol of the  
59 best-effort class at a timing at which there is no data conforming to  
60 said first protocol from said weighting scheduler;  
61 a protocol converter for converting the data conforming to said first  
62 protocol after said scheduling apparatus has shaped the transmission rate  
63 therefor to data conforming to said second protocol; and  
64 a multiplexer including a current data detector for supplying said  
65 scheduling apparatus with said rate information as indicative of a currently set  
66 reception rate for said user terminals, said multiplexer being configured to  
67 perform DSL processing using telephone lines to transmit to each of said user  
68 terminals the data conforming to said second protocol from said protocol  
69 converter or the data conforming to said first protocol after said scheduling  
70 apparatus has shaped the transmission rate therefor.



1 6. (Original) A network connection system for connecting a first  
2 communication network and a plurality of user terminals when a second  
3 communication network is interposed between said first communication  
4 network and said plurality of user terminals, said second communication  
5 network employing a second protocol different from a first protocol employed  
6 in said first communication network, said system comprising:

7 a scheduling apparatus including:

8 a classification processing unit for classifying data conforming  
9 to said first protocol received from said communication network based  
10 on quality guaranteed classes set thereto;

11 an overhead amount correction unit for correcting an overhead  
12 amount between a rate based on said second protocol and a rate based  
13 on said first protocol to convert received rate information on said  
14 second protocol to the rate based on said first protocol;

15 a weighting coefficient calculation unit for calculating a  
16 weighting coefficient based on said rate calculated by said overhead  
17 amount correction unit and the transmission rate for a preferential class  
18 among said classified classes using information fed back from said  
19 user terminals such that a minimally guaranteed rate is assured for the  
20 minimum rate guaranteed class among the classes classified by said  
21 classification processing unit;

22 a weighting scheduler for scheduling data conforming to said  
23 first protocol of said minimum rate guaranteed class and of a  
24 weighting applied class among said classified classes based on the  
25 weighting coefficient calculated by said weighting coefficient  
26 calculation unit to deliver the data in accordance with the scheduling;  
27 and

28 a preferential control scheduler for scheduling the data  
29 conforming to said first protocol of said preferential class, the data  
30 conforming to said first protocol from said weighting scheduler, and  
31 data conforming to said first protocol of a best-effort class among said  
32 classified classes such that the data conforming to said first protocol is  
33 delivered at a transmission rate equal to or lower than said rate  
34 calculated by said overhead amount correction unit, and for  
35 preferentially scheduling the data conforming to said first protocol of  
36 said preferential class, preferentially scheduling the data conforming to  
37 said first protocol from said weighting scheduler at a timing at which  
38 there is no data conforming to said first protocol of said preferential  
39 class, and delivering the data conforming to said first protocol of the  
40 best-effort class at a timing at which there is no data conforming to  
41 said first protocol from said weighting scheduler;  
42 a protocol converter for converting the data conforming to said first  
43 protocol after said scheduling apparatus has shaped the transmission rate  
44 therefor to data conforming to said second protocol; and  
45 a multiplexer including a current data detector for supplying said  
46 scheduling apparatus with said rate information as indicative of a currently set  
47 reception rate for said user terminals, said multiplexer being configured to  
48 perform DSL processing using telephone lines to transmit to each of said user  
49 terminals the data conforming to said second protocol from said protocol  
50 converter or the data conforming to said first protocol after said scheduling  
51 apparatus has shaped the transmission rate therefor.

1 7. (Original) A network connection system for connecting a first  
2 communication network and a plurality of user terminals when a second  
3 communication network is interposed between said first communication

NEC04P018-H1a

**AFTER FINAL: EXPEDITED ACTION**

01480088aa

Amendment dated 08/26/2008

Reply to office action mailed 06/09/2008

network and said plurality of user terminals, said second communication network employing a second protocol different from a first protocol employed in said first communication network, said system comprising:

a scheduling apparatus including:

a classification processing unit for classifying data conforming to said first protocol received from said communication network based on quality guaranteed classes set thereto;

an overhead amount correction unit for correcting an overhead amount between a rate based on said second protocol and a rate based on said first protocol to convert received rate information on said second protocol to the rate based on said first protocol;

a preferential class upper limit setting unit, operative when the difference between the transmission rate for a preferential class among said classified classes determined to be using information fed back from said user terminals and said rate calculated by said overhead amount correction unit is lower than a minimally guaranteed rate for a minimum rate guaranteed class among the classes classified by said classification processing unit, for setting an upper limit to the transmission rate for said preferential class for shaping such that the minimally guaranteed rate can be assured for said minimum rate guaranteed class;

a weighting coefficient calculation unit, operative when said preferential class upper limit setting unit does not set the upper limit, for calculating a weighting coefficient based on said rate calculated by said overhead amount correction unit and the transmission rate for the preferential class such that the minimally guaranteed rate is assured for said minimum rate guaranteed class, said weighting coefficient calculation unit being further operative when said preferential class

NEC04P018-H1a

**AFTER FINAL: EXPEDITED ACTION**

01480088aa

Amendment dated 08/26/2008

Reply to office action mailed 06/09/2008

upper limit setting unit sets the upper limit, for calculating a weighting coefficient based on said rate calculated by said overhead amount correction unit and the upper limit rate set by said preferential class upper limit setting unit such that the minimally guaranteed rate is assured for said minimum rate guaranteed class;

a weighting scheduler for scheduling data conforming to said first protocol of said minimum rate guaranteed class and of a weighting applied class among said classified classes based on the weighting coefficient calculated by said weighting coefficient calculation unit to deliver the data in accordance with the scheduling; and

a preferential control scheduler for scheduling the data conforming to said first protocol of said preferential class, the data conforming to said first protocol from said weighting scheduler, and data conforming to said first protocol of a best-effort class among said classified classes such that the data conforming to said first protocol is delivered at a transmission rate equal to or lower than said rate calculated by said overhead amount correction unit, and for preferentially scheduling the data conforming to said first protocol of said preferential class, preferentially scheduling the data conforming to said first protocol from said weighting scheduler at a timing at which there is no data conforming to said first protocol of said preferential class, and delivering the data conforming to said first protocol of the best-effort class at a timing at which there is no data conforming to said first protocol from said weighting scheduler;

a protocol converter for converting the data conforming to said first protocol after said scheduling apparatus has shaped the transmission rate therefor to data conforming to said second protocol; and

60           a multiplexer including a current data detector for supplying said  
61           scheduling apparatus with said rate information as indicative of a currently set  
62           reception rate for said user terminals, said multiplexer being configured to  
63           perform DSL processing using telephone lines to transmit to each of said user  
64           terminals the data conforming to said second protocol from said protocol  
65           converter or the data conforming to said first protocol after said scheduling  
66           apparatus has shaped the transmission rate therefor.

1           8-11. (canceled)

1           12. (original) A traffic shaping method, in a network connection system for  
2           connecting a communication network and a plurality of user terminals, for  
3           shaping a transmission rate for data conforming to a first protocol from said  
4           communication network, said method comprising the steps of:

5                 classifying data conforming to said first protocol received from said  
6                 communication network based on quality guaranteed classes set thereto;

7                 correcting an overhead amount between a rate based on a second  
8                 protocol and a rate based on said first protocol to convert received rate  
9                 information on said second protocol to the rate based on said first protocol;

10                calculating a weighting coefficient such that a minimally guaranteed  
11                rate is assured for a minimum rate guaranteed class among said classified  
12                classes based on said calculated rate;

13                scheduling data conforming to said first protocol of said minimum rate  
14                guaranteed class and of a weighting applied class among said classified classes  
15                based on the calculated weighting coefficient to deliver the data in accordance  
16                with the scheduling; and

17                scheduling the data conforming to said first protocol after said  
18                weighting, and data conforming to said first protocol of a best-effort class

19 among said classified classes, such that the data conforming to said first  
20 protocol is delivered at a transmission rate equal to or lower than said  
21 calculated rate, and for preferentially scheduling the data conforming to said  
22 first protocol after said weighting, so that the data conforming to said first  
23 protocol of said best effort class is delivered at a timing at which there is no  
24 data conforming to said first protocol after said weighting.

1 13. (canceled)

1 14. (original) A traffic shaping method, in a network connection system for  
2 connecting a communication network and a plurality of user terminals, for  
3 shaping a transmission rate for data conforming to a first protocol from said  
4 communication network, said method comprising the steps of:  
5 classifying data conforming to said first protocol received from said  
6 communication network based on quality guaranteed classes set thereto;  
7 measuring a transmission rate for a preferential class among said  
8 classified classes;  
9 correcting an overhead amount between a rate based on a second  
10 protocol and a rate based on said first protocol to convert received rate  
11 information on said second protocol to the rate based on said first protocol;  
12 calculating a weighting coefficient based on said calculated rate and  
13 the transmission rate measured for the preferential class such that a minimally  
14 guaranteed rate is assured for a minimum rate guaranteed class among the  
15 classified classes;  
16 scheduling data conforming to said first protocol of said minimum rate  
17 guaranteed class and of a weighting applied class among said classified classes  
18 based on the calculated weighting coefficient to deliver the data in accordance  
19 with the scheduling; and

20 scheduling the data conforming to said first protocol of said  
21 preferential class, the data conforming to said first protocol after said  
22 weighting, and data conforming to said first protocol of a best-effort class  
23 among said classified classes such that the data conforming to said first  
24 protocol is delivered at a transmission rate equal to or lower than said  
25 calculated rate, and for preferentially scheduling the data conforming to said  
26 first protocol of said preferential class, preferentially scheduling the data  
27 conforming to said first protocol after said weighting at a timing at which  
28 there is no data conforming to said first protocol of said preferential class, and  
29 delivering the data conforming to said first protocol of the best-effort class at a  
30 timing at which there is no data conforming to said first protocol after said  
31 weighting.

1 15. (original) A traffic shaping method, in a network connection system for  
2 connecting a communication network and a plurality of user terminals, for  
3 shaping a transmission rate for data conforming to a first protocol from said  
4 communication network, said method comprising the steps of:

5 classifying data conforming to said first protocol received from said  
6 communication network based on quality guaranteed classes set thereto;

7 measuring a transmission rate for a preferential class among said  
8 classified classes;

9 correcting an overhead amount between a rate based on said second  
10 protocol and a rate based on said first protocol to convert received rate  
11 information on said second protocol to the rate based on said first protocol;

12 when the difference between said measured transmission rate of the  
13 data conforming to said first protocol of the preferential class and said  
14 calculated rate is lower than a minimally guaranteed rate for a minimum rate  
15 guaranteed class among said classified classes, setting an upper limit to the

transmission rate for said preferential class for shaping such that the minimally  
guaranteed rate can be assured for said minimum rate guaranteed class;  
calculating a weighting coefficient based on said calculated rate and  
said transmission rate measured for the preferential class such that a minimally  
guaranteed rate is assured for said minimum rate guaranteed class, when the  
upper limit rate is not set for said preferential class, and calculating a  
weighting coefficient based on said calculated rate and said set upper limit rate  
such that the minimally guaranteed rate is assured for said minimum rate  
guaranteed class when the upper limit rate is set for said preferential class;  
scheduling data conforming to said first protocol of said minimum rate  
guaranteed class and of a weighting applied class among said classified classes  
based on said calculated weighting coefficient to deliver the data in  
accordance with the scheduling; and  
scheduling the data conforming to said first protocol of said  
preferential class, the data conforming to said first protocol after said  
weighting, and data conforming to said first protocol of a best-effort class  
among said classified classes such that the data conforming to said first  
protocol is delivered at a transmission rate equal to or lower than said  
calculated rate, preferentially scheduling the data conforming to said first  
protocol of said preferential class, preferentially scheduling the data  
conforming to said first protocol after said weighting at a timing at which  
there is no data conforming to said first protocol of said preferential class, and  
delivering the data conforming to said first protocol of the best-effort class at a  
timing at which there is no data conforming to said first protocol after said  
weighting.

16. (original) A traffic shaping method, in a network connection system for  
connecting a communication network and a plurality of user terminals, for



3       shaping a transmission rate for data conforming to a first protocol from said  
4       communication network, said method comprising the steps of:  
5             classifying data conforming to said first protocol received from said  
6       communication network based on quality guaranteed classes set thereto;  
7             correcting an overhead amount between a rate based on a second  
8       protocol and a rate based on said first protocol to convert received rate  
9       information on said second protocol to the rate based on said first protocol;  
10            calculating a weighting coefficient based on said calculated rate and  
11       the transmission rate for a preferential class among said classified classes  
12       determined to be using information fed back from said user terminals such that  
13       a minimally guaranteed rate is assured for a minimum rate guaranteed class  
14       among said classified classes;  
15            scheduling data conforming to said first protocol of said minimum rate  
16       guaranteed class and of a weighting applied class among said classified classes  
17       based on said calculated weighting coefficient; and  
18            scheduling the data conforming to said first protocol of said  
19       preferential class, the data conforming to said first protocol after said  
20       weighting, and data conforming to said first protocol of a best-effort class  
21       among said classified classes such that the data conforming to said first  
22       protocol is delivered at a transmission rate equal to or lower than said  
23       calculated rate, preferentially scheduling the data conforming to said first  
24       protocol of said preferential class, preferentially scheduling the data  
25       conforming to said first protocol after said weighting at a timing at which  
26       there is no data conforming to said first protocol of said preferential class, and  
27       delivering the data conforming to said first protocol of the best-effort class at a  
28       timing at which there is no data conforming to said first protocol after said  
29       weighting.

1 17. (original) A traffic shaping method, in a network connection system for  
2 connecting a communication network and a plurality of user terminals, for  
3 shaping a transmission rate for data conforming to a first protocol from said  
4 communication network, said method comprising the steps of:

5 classifying data conforming to said first protocol received from said  
6 communication network based on quality guaranteed classes set thereto;

7 correcting an overhead amount between a rate based on a second  
8 protocol and a rate based on said first protocol to convert received rate  
9 information on said second protocol to the rate based on said first protocol;

10 when the difference between the transmission rate for a preferential  
11 class among said classified classes determined using information fed back  
12 from said user terminals and said calculated rate is lower than a minimally  
13 guaranteed rate for a minimum rate guaranteed class among said classified  
14 classes, setting an upper limit to the transmission rate for said preferential  
15 class for shaping such that the minimally guaranteed rate can be assured for  
16 said minimum rate guaranteed class;

17 calculating a weighting coefficient based on said calculated rate and  
18 the transmission rate for the preferential class such that the minimally  
19 guaranteed rate is assured for said minimum rate guaranteed class, when the  
20 upper limit rate is not set for said preferential class, and calculating a  
21 weighting coefficient based on said calculated rate and said upper limit rate set  
22 for said preferential class such that the minimally guaranteed rate is assured  
23 for said minimum rate guaranteed class, when the upper limit rate is set for  
24 said preferential class;

25 scheduling data conforming to said first protocol of said minimum rate  
26 guaranteed class and of a weighting applied class among said classified classes  
27 based on said calculated weighting coefficient; and

28 scheduling the data conforming to said first protocol of said  
29 preferential class, the data conforming to said first protocol after said  
30 weighting, and data conforming to said first protocol of a best-effort class  
31 among said classified classes such that the data conforming to said first  
32 protocol is transmitted at a transmission rate equal to or lower than said  
33 calculated rate, preferentially scheduling the data conforming to said first  
34 protocol of said preferential class, preferentially scheduling the data  
35 conforming to said first protocol after said weighting at a timing at which  
36 there is no data conforming to said first protocol of said preferential class, and  
37 delivering the data conforming to said first protocol of the best-effort class at a  
38 timing at which there is no data conforming to said first protocol after said  
39 weighting.

1 18. (original) The traffic shaping method according to claim 12, wherein said  
2 first communication network is an IP network, said data conforming to said  
3 first protocol is an IP packet, said second network is an ATM network, and  
4 said data conforming to said second protocol is an ATM cell.